



DECLARATION OF PERFORMANCE

1.	Identification/Serial Number	DS14 EN 1125
2.	Description	Timber Emergency Exit Door in a timber frame
3.	Intended Use	Escape Route
4.	Manufacturer Details	Performance Doorset Solutions (PDS) Unit 1a Greenvale Business Park Todmorden Road Littleborough OL15 9AZ
5.	Source Data	Incorporating EN12210 & EN12211 Wind load Resistance EN1027 & EN 12208 Water tightness EN1026 & EN 12207 Air Permeability EN ISO 10077-1:2000 Thermal Insulation
6.	Relevant Harmonised Standard	BS EN 145351-1:2006 + A1: 2010

DECLARED PERFORMANCE

	Characteristic	Declared Performance	Harmonised Standard
7.1	Water-tightness	NPD	EN 14351-1:2006 + A1: 2010
7.2	Air Permeability	NPD	
7.3	Resistance to wind-load	NPD	
7.4	Dangerous Substances	None	
7.5	Load-bearing Capacity of safety device	N/A	
7.6	Acoustic performance	NPD	
7.7	Thermal transmittance	<1.8W/m2K	
7.8	Radiation Properties	NPD	
7.9	Ability to Release	Emergency Exit panic hardware complies with EN 1125 when fitted	

The performance of the product Identified in points 1 and 2 conforms to the performance declared in point 7.1-7.9. This declaration is issued under the sole responsibility of the manufacturer identified in point 4.

Signed on behalf of the Manufacturer by:

09/08/2013

Ben Davies
Technical Assistant

Date